Safety

Catalog No.

300-2

Hot Socket Gap Indicator

The **TESCO Hot Socket Gap Indicator** is used to determine if a meter socket jaw has become wornout and unsafe for continued use. The Gap Indicator determines unsafe holding force on meter socket jaws based on laboratory testing.

The **TESCO Hot Socket Gap Indicator** is quick, easy-to-use and has a rugged, non-conductive

insulated shell. The mechanical tool engages the jaws of a meter socket and will indicate a gap or significant loss of jaw pre-load. Total estimated time of testing four jaws is less than 30 seconds. Even minor gaps can result in electrical arcing, resulting with a more serious problem, failure, or electrical fire.

- Easy-to-use design
- Determines unsafe holding-force on meter socket jaws based on laboratory testing
- Blade spring force was designed to effectively determine a minimum unsafe threshold
- Insulated plastic body (Rated 3000V)
- Tin-plated spring steel blade used to withstand daily use/travel/vibration
- No maintenance required
- Calibrated for 5 years or 1,000,000 sockets (whichever occurs first)





No indication of a "bad" socket gap/loss of spring force.



Red indication of a "bad" socket gap/loss of spring force.



TESCO METERING



925 Canal Street, Bristol, PA 19007 • ph: 215.228.0500 • tescometering.com